



SPB 16-30 Pipe Bending Machine

Operating weight	39,683 lbs / 18,000 kg
Max. Operating Pressure	4,060 p.s.i. / 280 bar
Horsepower	99.5 HP (with Cat engine)



SPB 16-30 PIPE BENDER


ABOUT THE SPB 16-30

The new pipe bending machine SPB 16-30 belongs to the "Millennium Series" fleet, which is the new generation of SUPERIOR pipe benders. Despite its simplicity this machine guarantees high performance in terms of speed and push.

The frame is made of high quality steel, and the parts mostly subject to stresses have been ribbed and boxed to ensure maximum resistance, though keeping the machine weight as light as possible.

The hydraulic system has 5 spools; the fifth spool may be used to control the hydraulic mandrel, if fitted. The separate valves enable the operator to set the mandrel pressure independently from the machine. The hydraulic cylinders are sized in such a way that they can operate with pressures exceeding 300 bar. The system design and the proportional valves offer excellent modularity and sensitivity of machine movements, at the same time making the machine speed and push very easy to control.

The SPB 16-30 is installed on tilting idle tracks. Its dimensions and low profile make its travel easy on any job site, thus being the best solution, especially on small- and medium-sized projects where 30" pipes are used.



SPECIFICATIONS

ENGINE

Model	Caterpillar C-4.4 ACERT
Net flywheel power (DIN 6271)	99.5 HP
Governed speed	2,000 rpm
Displacement	4.01 liters
Number of cylinders	4
Sound proofing type	Yes

HYDRAULIC PUMP

Type	Variable axial piston pump, with pressure and flow control
Maximum flow rate	40 U.S. gal/min - 150 lt/min
Maximum constant pressure	4,061 p.s.i. / 280 bar
Maximum peak pressure	5,046 p.s.i. / 350 bar

CONTROL VALVE

Brand	Rexroth
Type	Load-sensing with proportional control (LUDV)
Spools	N.5

HYDRAULIC WINCH

Type	Hydraulic winch
Maximum pull at first layer	9,700 lbs / 4,400 kg
Hydraulic motor	Orbital DANFOSS
Frame	Aluminum allow + ductile cast iron
Reduction gear	With worm screw, irreversible
Neutral	Manual
Maximum operating pressure	2,030 p.s.i. / 140 bar
Maximum feed flow rate	42 U.S. gal/min - 160 lt/min
Speed at first layer	16 ft/min - 4,85 m/min
Recommended cable diameter	1/2 inch / Ø 10 mm
Wire rope type	6 strands with textile core
R=2,160 N/mm2 min. breaking load guaranteed 30,000 kg	

HYDRAULIC OIL TANK

Type	Metal work with filter
Capacity	50 U.S. gal / 190 lt
Cartridge type	Donaldson

FUEL TANK

Type	Metal work with filter
Capacity	52 U.S. gal / 200 lt

SPOOLS

Spool 1: Out-board and in-board cylinders, clamp

Maximum flow	39.6 U.S. gal/min - 150 lt/min
Pressure	4,351 p.s.i. / 300 bar

Spool 2: Wedge cylinder

Maximum flow	40 U.S. gal/min - 150 lt/min
Pressure	2,175-4,351 p.s.i. / 150-300 ¹ bar

Spool 3: Winch

Maximum flow	26 U.S. gal/min - 100 lt/min
Pressure	2,320 p.s.i. / 160 bar

Spool 4: Auxiliary control 1

Maximum flow	26 U.S. gal/min - 100 lt/min
Pressure	2,320 p.s.i. / 160 ² bar

Spool 5: Auxiliary control 2

Maximum flow	26 U.S. gal/min - 100 lt/min
Pressure	1,740 p.s.i. / 140 ² bar

¹ Cylinder out / in pressure

² Adjustable

FEATURES



ENGINE


A choice of Caterpillar, Perkins, Deutz and Cummins diesel engines, all of which have many reliable and modern features, such as the water pump, integrated filtration system, and self-stretching fan towing seals.

The engine is enclosed in a sound reducing box and is located on the side opposite the operator.

It also complies with recent anti-pollution requirements in all of the industrialized nations. The engine compartment is cleverly designed to swing open to allow easier access to the engine for maintenance.

HYDRAULIC WINCHES

The hydraulic winches have a pulling capacity ranging from 3,000 to 10,000 Kg. The free drum control is located in the control panel on the operator's platform.



HYDRAULIC SYSTEM

New operator friendly hydraulic system with a load-sensing variable pump and a five-spool proportional valve, allowing much safer, faster and more precise control of movements. The new valve which was only recently introduced to the market allows the regulation of the pressure and the capacity of each function according to its purpose.

The three largest machines have an automatic power controlling system allowing a quick approach and a progressive slowing down when close to the maximum push. The hydraulic system features high quality components manufactured by Mannesmann Rexroth or Parker-Voac. All these components contribute to higher productivity and a reduction in power consumption.

The Millennium Series also has stronger hydraulic cylinders that have been tested to work at high pressures. The cylinders have molybdenum chromium-plated steel piston rods with components made to bear high pressure to 6,000 PSI.

OPERATOR'S PLATFORM

The position of the piloting platform and the engine compartment on opposite sides make this machine unique in terms of operating comfort and guarantee maximum visibility and low noise levels to the operator.



TRACKS

Caterpillar-type crawler undercarriages with triple grouser bars on industrial-grade shoes. A hydraulic cylinder controls the tensioning of the tracks, as on all earth-moving tractors.

ROLLERS

Pipe drive rollers are mounted on non-friction bearing and coated with 90 SH polyurethane for smoother handling of the pipe.



FRAME

The main frame is built with high quality steel plate and box-section design. This makes the machine stronger and more resistant to stresses, thus permitting bending of pipes with very high tensile strength.



BENDING DATA

U.S.


Pipe O.D. inch	Maximum Wall Thickness By Grade (Inch)							Recommended Bend		
	X52	X56	X60	X65	X70	X80	X100	Degree per Arc Foot	Radius Feet	Max Degree Per 40 Feet
16	2	2	2	2	2	2	2	1.51	38	40.80
18	2	2	2	2	2	2	1-11/16	1.10	52	29.70
20	2	2	2	2	1-15/16	1-7/8	1-9/16	0.90	64	24.40
22	2	1-15/16	1-3/4	1-5/8	1-7/16	1-1/4	15/16	0.80	72	21.60
24	1-5/8	1-1/2	1-3/8	1-1/4	1-1/8	1	3/4	0.75	76	20.25
26	1-5/16	1-3/16	1-1/8	1	15/16	13/16	5/8	0.70	82	18.90
28	1-1/8	1	15/16	7/8	3/4	11/16	1/2	0.65	88	17.60
30	15/16	7/8	13/16	3/4	11/16	9/16	7/16	0.60	96	16.20

METRIC


Pipe O.D. inch/mm	Maximum Wall Thickness By Grade (Inch)							Recommended Bend		
	X52	X56	X60	X65	X70	X80	X100	Ratio Radius: O.D.	Radius Meter	Max Degree Per 12 Meters
16 / 406.4	50.80	50.80	50.80	50.80	50.80	50.80	50.80	28.5	11.58	40.80
18 / 457.2	50.80	50.80	50.80	50.80	50.80	50.80	42.87	34.7	15.85	29.70
20 / 508	50.80	50.80	50.80	50.80	50.80	50.80	39.69	38.4	19.51	24.40
22 / 558.8	50.80	49.22	44.45	41.28	36.52	31.75	23.82	39.3	21.95	21.60
24 / 609.6	41.28	38.10	34.93	31.75	28.58	25.40	19.05	38.0	23.16	20.25
26 / 660.4	33.34	30.17	28.58	25.40	23.82	20.64	15.88	37.9	24.99	18.90
28 / 711.2	28.58	25.40	23.82	22.23	19.05	17.47	12.70	37.7	26.82	17.6
30 / 762	23.82	22.23	20.64	19.05	17.47	14.29	11.12	38.4	29.26	16.20

DIMENSIONS

Operating weight 39,683 lbs / 18,000 kg



	Feet	Meters
A Overall length	22.3 ft	6.8 m
B Overall width	8 ft	2.45 m
C Height	7.7 ft	2.35 m
D Width to outside of tracks	7.74 ft	2.36 m
E Length of front section	4.1 ft	1.26 m
F Length of undercarriage touching the ground	3.66 ft	1.12 m
G Length of middle section	7.6 ft	2.33 m
H Length of track on the ground	4.11 ft	1.26 m
I Length of rear section	2.75 ft	84 cm
J Height to bottom of cradle	1.6 ft	50 cm
K Height to top of roller	2.8 ft	86 cm
L Length of hitch	1.7 ft	51 cm
M Ground clearance	1.15 ft	35 cm
Track weight (loose pair) 4,000 lbs / 1,800 kg		



BENDING STRENGTH

Here's an example of our pipe bending machines high bending strength. The bending performance data shown was calculated using **API X80** as an example. The machine is capable of bending all grades of currently available API-5L pipe within its range.



ACCURACY-BEND SYSTEM



ACCURATE BENDING MADE EASY

This equipment consists of three different parts; one of which will have to be fitted on the machine control platform and two at the ends of the pipe to be bent. These two end parts are to be secured to the pipe by means of magnet plates. The electronic components are placed inside a housing made with steel and strong plastic material (polyurethane).

The box on the control platform will be equipped with a high-luminosity display (easy to see even on very sunny



days), showing 4 digits, two of them being decimals.

All the components are made of extremely durable and high quality material designed to withstand heavy-duty applications, and wide temperature variations of -30°C to $+80^{\circ}\text{C}$.


The level of precision of this device is 1/50 grade. Its battery life is approximately 70 hours before requiring recharging.

ARCTIC PACKAGE

Not available for the SPB 6-20



STANDARD WINTERIZATION FOR -30°C TEMPERATURES



- A. Heater group for hydraulic tank (220 Volt - 110 Volt). Immersion type, 750 Watts.
- B. Heater group for the engine (220 Volt - 110 Volt). Immersion type, 750 Watts.
- C. External plastic sheeting over engine box with radiator side part to be rolled up if needed.
- D. Oversized battery.
- E. Very fluid engine oil: SAE 10W20 for low temperatures.
- F. Heavy oil tank condensation discharge.
- G. Hydraulic oil temperature gauge.
- H. Higher setting of engine power.
- I. Shut off group.

RECOMENDATIONS FOR MACHINE OPERATION

- Use only arctic fuel; see Caterpillar book.
Use only arctic type fuel as recommended by manufacturer.
- Warm up the hydraulic oil and coolant sufficiently before starting the diesel engine.
- Let engine run for a few minutes and then engage hydraulics without bending any pipe.
- For the first 15 minutes, let the engine turn at idle power before starting bending operations.
- Bend pipe carefully and thoroughly, and if temperatures are very low, perform all movements slowly.

FEATURES

- Built with high quality steel
- Cab lined with insulation for noise and temperature abatement control
- Maximum visibility
- Side windows protected with steel grids
- Side windows equipped with windshield wipers
- Available with heater or air conditioning
- Pressurized cab available

AVAILABLE MODELS



SPB 6-20 Millennium Series



SPB 16-30 Millennium Series



SPB 22-36 Millennium Series



SPB 32-42 Millennium Series



SPB 36-48 Millennium Series



SPB 48-60 Millennium Series

CONTACT INFORMATION

Europe

Phone +49.0.231.963.3073

pipelinece@wwmach.com

Russia, China and the Middle East

Phone +39.349.198.1281 Italy

Phone +7.495.507.4827 Russia

fsupipeline@wwmach.com

India

Phone +91.11.414.59230

pipelineind@wwmach.com

Africa

Intl. Toll Free 800.9675.3948

pipeline@wwmach.com

North America

Phone +1.281.457.4400

pipelinea@wwmach.com

Latin America

Phone +52.81.8.394.0160

pipelinesa@wwmach.com

Brazil

Phone 800.9675.3948

pipelinebr@wwmach.com

Australia

Phone +61.0.400.144.432

pipelinece@wwmach.com



16031 East Freeway

Houston, TX 77530

Phone 281.457.4400 Fax 281.452.5455

U.S. Toll Free 800.383.2666 Intl. Toll Free 800.9675.3948

pipeline@wwmach.com

www.worldwidemachinery.com